

# Smart business solutions

The IM 600F and IM 600SRF are intelligent and always current devices. Cloud-enabled, they will adapt seamlessly to your changing business needs.

### Cloud-enabled 4-in-1 MFPs

- Print, copy, scan & fax
- Single-pass scanning
- Internal staple finisher
- Regular firmware upgrades

These versatile 4-in-1 MFPs can print, copy, scan and fax. They are also Cloud enabled. Using the integral SPDF (Single Pass Document Feeder), double sided originals can be scanned in a single pass and uploaded to Cloud-share services, such as DropBox™ and Sharepoint™. The IM 600SRF also features a compact internal finisher, which neatly collates and staples document sets.

## **Super-sized Smart Operation Panel**

- Intuitive user interface
- Time-saving Smart apps
- Secure authentication
- Ricoh Smart Integration



Effortlessly productive, these A4 mono MFPs will meet the most demanding high speed / high volume requirements. To improve workflow speed, the first immaculate 1.200dpi print is ready in 2.4 seconds and multipage document sets are delivered at a highly productive 60 ppm. With their long-life imaging drums offering maintenance free performance, reliability is a given. And, with stacks of paper on line and the MFPs switching seamlessly between trays, there is seldom any need to stop.

### Productive and reliable performance

- 1200 dpi resolution
- Fast 60 ppm throughput
- 2600 sheet capacity (max)
- Maintenance-free to 500k

Ricoh's Smart Operation Panel empowers users. Employees can connect seamlessly to the MFP and print from / scan to smartphones and tablets. Confidential documents can be password protected and held pending release. And, with tap and go authentication, information security is assured. The Smart Operation Panel also supports enterprise workflow solutions, such as Streamline NX. With Ricoh Smart Integration, new applications can be added as your business requirements change.



# RICOH IM 600F/IM 600SRF

MAIN SPECIFICATIONS

GENERAL	IM 600F	IM 600SRF
Warm-up time	25.4 seconds	
First output speed: B/W	25.4 seconds 2.4 seconds	
Continuous output speed	60 ppm	
Memory: standard	2 GB	
Memory: maximum	2 GB	
HDD: standard	320 GB	
Weight	29 kg	40 kg
Dimensions: W x D x H	480 x 539 x 644 mm	480 x 543 x 740 mm
Power source	220 - 240 V,	50 - 60 Hz
COPIER		
Multiple copying	Up to 999	•
Resolution	600 x 600 dpi	
Enlargement/reduction	50 - 200%	
Zoom	From 25% to 400	% in 1% steps
PRINTER		
CPU	Intel® Apollo Lake P	
Printer language: standard	PCL5e, PCL6(XL), PostScript 3 (er	
Printer language: option	Genuine Adobe®	PostScript®3™
Print resolution: maximum	1,200 x 1,2	
Protocol	TCP/IP, IF	
Security	WEP, WPA	A, WPA2
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host Type A, USB Host Type miniB, Bluetooth, Wireless LAN (IEEE 802.11 a/b/g/n/ac), USB Host I/F, USB Device 2.0, SD slot, USB Media Slot, Micro SD Card Slot, NFC tag	
Network interface: option	Bi-directional Wireless LAN (IEE USB Device So	E 802.11a/b/g/n)
Mobile printing capability	Apple AirPrint, Mopria®, Google Cloud Print	•
Network protocol	TCP/IP (IP v4, IP v6)	
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Serve	
Mac OS environments	Macintosh OS X Nat	
UNIX environments SAP® environments	UNIX Sun® Solaris (10), HP-UX (11.x, 11i v2, 11i v3), 5.0.7, 6.0 SAP® R	
SCANNER		
Simplex:	BW60 ipm (A	
	Colour40 ipm (	• •
Duplex:	BW100 ipm (A	• •
Decelution, marries un	Colour62 ipm (	
Resolution: maximum		
Compression method	BW: TIFF (MH, MR, MMR, JBIG Colour: 、	
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page Multi page PDF, Multi page High con	
Scan modes	E-mail, Folder, USB, SD Ca	
FAX		
PSTN, PBX		
Compatibility	ITU-T (CC	•
Transmission speed	2 seco	
Modem speed: maximum	33.6 K	•
Resolution: standard	8x7.7 line/mm,	·
Compression method	MH, MR, MMR, JBIG, N	
Scanning speed	61 sp	
Page memory size	Standard With optional SAE	
SAF memory size	With optional SAF Standard: 4 MB (appro	
On Highlory SIZE	Standard: 4 MB (appro Optional: 60 MB (approx	, , , ,
PAPER HANDLING		
	A4, A5, A6	, B5, B6
Recommended paper size		
	600 sh	eets
Paper input: standard	600 sh 2,600 sl	
Paper input: standard Paper input: maximum		neets
Recommended paper size Paper input: standard Paper input: maximum Paper output: standard Paper output: maximum	2,600 st	neets
Paper input: standard Paper input: maximum Paper output: standard	2,600 st 500 sh	neets eets eets

## RICOH IM 600F/IM 600SRF

MAIN SPECIFICATIONS

IM 600F IM 600SRF

Power consumption: max. Less than 1,500 W

Power consumption: operation 758 W Power consumption: ready 88 W Less than 1,500 W 749 W 93.8 W

0.65 W

TEC\* 0.84 kWh/week

\* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

Power consumption: sleep

#### SOFTWARE

**ECOLOGY** 

@Remote, Streamline NX v3, device management only (not embedded), Device Manager NX

#### **OUTPUT TRAYS AND FINISHER OPTIONS**

4x 500-sheet paper tray 50-sheet Internal finisher (IM 600SRF)

Consumable yield measuring method ISO/IEC 19798

#### OTHER OPTIONS

Fax connection unit, High cabinet, Low cabinet, Caster table, VM card, Device server unit, File format converter, OCR unit, Enhanced security HDD, Data overwrite security unit, NFC card reader

#### CONSUMABLES

Starter toner	11,000 prints
Toner (regular yield)	25,500 prints
Toner (high yield)	40,000 prints



















# Ricoh Denmark A/S

Delta Park 37 2665 Vallensbæk Strand Denmark



+45 70 10 67 68



www.ricoh.dk

Copytec Office Solutions ApS Gunnar Clausens Vej 7 8260 Viby J Denmark +45 86 11 40 11 www.copytec.dk



