

# Robust A4 print solutions

These A4 printers set new benchmarks for speed and resilience. Their robust performance will enhance productivity and enable your business to meet critical deadlines.

### Productive, non-stop performance

- 55 & 60 ppm print speeds
- Non-stop performance
- Up to 2600 sheets
- 1200 dpi image quality

Running at speeds of 55 and 60 pages a minute and with stacks of paper on line, Ricoh's P 800 and P 801 mono A4 printers will easily handle the most demanding high speed / high volume workgroup print requirements. And, what is more, with their long-life parts and high yield toner cartridges offering hassle-free and maintenance-free performance, they will go on and on and on.

### Powerful Intel-based controller

- · Fast job processing
- · Uniform workflow
- Remote support
- Tap and go security



When productivity matters, the Ricoh P 800 and P 801 deliver. With their Intel processors effortlessly handling complex PCL and PostScript files, the first 1,200 dpi print is ready in 2.4 seconds. The advanced controller provides a uniform workflow across compatible Ricoh devices and can be used to run enterprise workflow solutions, such as Streamline NX. And, with Near Field Communication (NFC) a standard feature, secure authentication is as easy as tap and go.

#### Quietly effective and affordable

- Space-saving design
- BAM compliant
- Maintenance free
- Low running costs

These A4 printers can be positioned at the very heart of your operation. Compact, easy to use and utterly reliable, they produce high quality print communication, quickly and without fuss. The energy efficient printers comply with Blue Angel Mark (BAM) environmental standards, and with their long-life parts offering maintenance-free performance and high yield toner cartridges reducing running costs, they are arguably the most effective and affordable A4 mono printers available today.



# **RICOH P 800/P 801**

## MAIN SPECIFICATIONS

	P 800		P 801
GENERAL			
Warm-up time		25.4 seconds	
First output speed: B/W		2.4 seconds	00
Continuous output speed Memory: standard	55 ppm	2 GB	60 ppm
Memory: maximum		2 GB	
HDD: option		320 GB	
Weight		18 kg	
Dimensions: W x D x H	420 x 410 x 345 mm		443 x 410 x 365 mm
Power source		220 - 240 V, 50/60 Hz	
PRINTER			
CPU	Intel®	Atom Processor ApolloLake:1.3 GH	lz
Printer language: standard		PCL5c PCL5e	
		PCL6	
		PostScript 3 (emulation)	
Printer language: option	(	Genuine Adobe ®PostScript®3™	
		IPDS PDF Direct from Adobe®	
Print resolution		1,200 x 1,200 dpi	
Network interface: standard	Ethern	et 10 base-T/100 base-TX/1000 base	e-T
	2310111	USB2.0	
		NFC Tag	
Network interface: option	NA.	Bi-directional IEEE 1284/ECP	
		Vireless LAN (IEEE 802.11a/b/g/n) Server for Second Network Interface	
Mobile printing capability	005	Apple AirPrint	
		Mopria®	
		Google Cloud Print NFC	
		Ricoh Smart Device Print & Scan	
		Ricoh Smart Device Connector	
Windows® environments		Windows® 7	
		Windows® 8.1 Windows® 10	
		Windows® Server 2008	
		Windows® Server 2012	
		Windows® Server 2012R2 Windows® Server 2016	
Mac OS environments	Ma	cintosh OS X Native v10.11 or later	
UNIX environments	IVIO	UNIX Sun® Solaris10	
		HP-UX11.x11i v211i v3	
		SCO OpenServer5.0.76.0	
SAP® environments		RedHat® Linux Enterprise456	
SAP® environments		SAP® R/3® SAP® S/4®	
DARER HANDING			
PAPER HANDLING			
Recommended paper size		A4 A5	
		A5 A6	
		B5	
Demonistrate dend		B6	
Paper input: bypass		600 sheets	
Paper input: bypass Paper input: maximum		100 sheets 2,600 sheets	
Paper output: standard		500 sheets	
Paper output: maximum		500 sheets	
Paper weight		Trays:64 - 120 g/m²	
		Bypass:60 - 220 g/m²	
Paper tunes		Duplex:64 - 120 g/m²	
Paper types		Plain paper Recycle paper	
		Special paper	
		Color paper	
		Letterhead Cardstock	
		Preprinted paper	
		Bond paper	
		Coated paper	
		Envelope Gloss paper	
		Label paper	
		Thick paper	
		OHP	

# **RICOH P 800/P 801**

### MAIN SPECIFICATIONS

	P 800		P 801	
ECOLOGY				
Power consumption: max.		Less than 1,400 W		
Power consumption: operation	716 W		749 W	
Power consumption: sleep		0.48 W		
TEC*	0.74 kWh		0.81 kWh	
* It is a reference value based on				
the ENERGY STAR Ver.3.0 test				
method.				
OUTPUT TRAYS OPTIONS				
4x 500-sheet Paper tray				
CONSUMABLES				
Starter toner	10,000 prints		11,000 prints	
Drum		500,000 sheets		
Toner (regular yield)		25,500 prints		
Toner (ultra high yield) (P 801)	-		40,000 prints	
Consumable yield measuring				
method ISO/IEC 19752				













### Ricoh Denmark A/S

Delta Park 37 2665 Vallensbæk Strand Denmark



+45 70 10 67 68



www.ricoh.dk

Copytec Office Solutions ApS Gunnar Clausens Vej 7 8260 Viby J Denmark +45 86 11 40 11 www.copytec.dk



